

SEE ATTACHMENT

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic diagram of a surge detection system according to a first embodiment of this invention.

Fig. 2 is a more detailed schematic diagram of a surge detection system of Fig. 1.

5 Fig. 3 is a chart showing an exemplary set of temperature measurements utilized in accordance with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention pertains to a method and apparatus for detecting surge in a
10 compressor of a compressor-driven system. A compressor-driven refrigeration system is an example of such a system. Fig. 1 is a schematic diagram of a surge detection system according to a first embodiment of this invention. In Fig. 1, reference symbol 10 designates a basic refrigeration system. As shown in Fig. 1, the refrigeration system 10 comprises a centrifugal compressor 20, having a suction side 25 and a discharge side 30 and a compressor impeller (not
15 shown). A discharge side conduit 35 connects discharge side 30 to a condenser 40. The compressor compresses the refrigerant and delivers the compressed gas to condenser 40. Condenser 40 includes a heat-exchange coil 45 having an inlet 50 and an outlet 55 connected to a cooling tower 60 or other cooling system that circulates a cooling fluid, such as water, through the heat exchange coil 45. The refrigerant flowing through condenser 40 exchanges heat with
20 the cooling fluid circulating through heat-exchange coil 45 causing the compressed gas to condense to a liquid refrigerant.

The patent or application file contains at least one drawing executed in color. Copies of this patent or patent application publication with color drawing(s) will be provided by the Office upon request and payment of the necessary fee.